


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:219.03V I:0.0663A P:14.694W PF:0.9644 Freq:49.99Hz Lamp Flux:1624.07x1 lm		
NAME: GLM-DOS260D-3000K-15W	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 110.52 lm/W			
MODEL		I _{max} (cd)	661.2	S/MH (C0/180)	1.18
NOMINAL POWER(W)		LOR(%)	100.0	S/MH (C90/270)	1.20
RATED VOLTAGE(V)	220.0	TOTAL FLUX(lm)	1624.1	η UP,DN (C0-180)	0.0,51.0
NOMINAL FLUX(lm)	1624.07	CIE CLASS	DIRECT	η UP,DN (C180-360)	0.0,49.0
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE (V)	220	η down (%)	100.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



H(β) Range: -90 - 90 DEG
H(β) Interval: 1.0 DEG
Test Speed: HIGH
Temperature: 25.3 DEG
Operators:
Test Date: 28 September 2023

V(B) Range: -75 - 75 DEG
V(B) Interval: 5.0 DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity: 65.0%
Test Distance: 8.000m [K=1.0875]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	647.2	641.6	641.6	636.9	643.2	633.2	636.6	638.3	0- 10	61.82	61.82	3.81,3.81
20	602.7	608.2	602.1	598.2	595.7	590.5	592.7	601.9	10- 20	175.3	237.1	14.6,14.6
30	532.4	535.1	542.6	526.3	522.7	515.3	529.6	526.0	20- 30	259.8	496.9	30.6,30.6
40	443.0	453.0	456.1	446.0	431.6	431.8	439.8	441.3	30- 40	304.0	800.9	49.3,49.3
50	340.7	350.9	361.5	345.6	329.7	330.0	343.2	337.2	40- 50	302.7	1104	68,68
60	231.0	246.4	258.7	240.7	222.9	224.7	239.6	231.0	50- 60	258.8	1362	83.9,83.9
70	118.5	141.9	153.4	133.1	114.4	118.2	134.3	124.3	60- 70	180.6	1543	95,95
80	12.81	37.75	0	28.87	10.86	18.66	0	21.59	70- 80	78.93	1622	99.9,99.9
90	0	0	0	0	0	0	0	0	80- 90	2.139	1624	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 955.12 lm

%lum = 58.8%

%lamp = 58.8%

Conical surface Flux(120deg): 1362.4 lm

%lum = 83.9%


%lamp = 83.9%

H(β) Range:-90 - 90DEG
 H(β) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:28 September 2023

V(B) Range:-75 - 75DEG
 V(B) Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:8.000m [K=1.0875]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:219.03V I:0.0663A P:14.694W PF:0.9644 Freq:49.99Hz Lamp Flux:1624.07x1 lm		
NAME: GLM-DOS260D-3000K-15W	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	0	0
80	1091	0
75	3682	5754
70	5123	6634
65	6077	7212
60	6835	7655
55	7397	7997
50	7841	8320
45	8226	8636


H(β) Range:-90 - 90DEG
 H(β) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:28 September 2023

V(B) Range:-75 - 75DEG
 V(B) Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:8.000m [K=1.0875]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:219.03V I:0.0663A P:14.694W PF:0.9644 Freq:49.99Hz Lamp Flux:1624.07x1 lm		
NAME: GLM-DOS260D-3000K-15W	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	Coefficients of Utilization(CU)															
RCR:Room Cavity Ratio																
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.06	1.02	.98	1.03	.90	.97	.99	.96	.94	.95	.93	.91	.92	.90	.88	.86
2.0	.93	.87	.81	.91	.85	.80	.88	.83	.78	.84	.80	.77	.81	.78	.75	.73
3.0	.82	.74	.68	.80	.73	.68	.78	.71	.66	.75	.70	.65	.72	.68	.64	.62
4.0	.73	.65	.58	.72	.64	.58	.69	.62	.57	.67	.61	.56	.65	.60	.56	.53
5.0	.65	.57	.50	.64	.56	.50	.62	.55	.50	.60	.54	.49	.58	.53	.49	.46
6.0	.59	.50	.44	.58	.50	.44	.56	.49	.44	.55	.48	.43	.53	.47	.43	.41
7.0	.54	.45	.39	.53	.45	.39	.51	.44	.39	.50	.43	.38	.49	.43	.38	.36
8.0	.49	.41	.35	.48	.40	.35	.47	.40	.35	.46	.39	.35	.45	.39	.34	.32
9.0	.45	.37	.32	.44	.37	.32	.43	.36	.31	.42	.36	.31	.41	.35	.31	.29
10.0	.42	.34	.29	.41	.34	.29	.40	.33	.29	.39	.33	.28	.38	.33	.28	.27


H(β) Range:-90 - 90DEG

H(β) Interval: 1.0DEG

Test Speed: HIGH

Temperature:25.3DEG

Operators:

Test Date:28 September 2023

V(B) Range:-75 - 75DEG

V(B) Interval: 5.0DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366

Humidity:65.0%

Test Distance:8.000m [K=1.0875]

Remarks:

WEC AND CCEC

Test:U:219.03V I:0.0663A P:14.694W PF:0.9644 Freq:49.99Hz Lamp Flux:1624.07x1 lm		
NAME: GLM-DOS260D-3000K-15W	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.276	.157	.050	.269	.153	.049	.256	.147	.047	.244	.141	.045	.233	.135	.043		
2.0	.268	.147	.045	.262	.144	.045	.251	.139	.043	.240	.135	.042	.230	.130	.041		
3.0	.253	.135	.040	.247	.133	.040	.237	.129	.039	.228	.125	.038	.219	.121	.038		
4.0	.236	.123	.036	.231	.121	.036	.222	.118	.035	.214	.115	.035	.206	.112	.034		
5.0	.220	.112	.032	.216	.111	.032	.208	.108	.032	.200	.106	.031	.193	.103	.031		
6.0	.205	.103	.029	.202	.102	.029	.194	.100	.029	.188	.098	.029	.182	.096	.028		
7.0	.192	.095	.027	.189	.094	.027	.182	.092	.027	.176	.090	.026	.171	.089	.026		
8.0	.180	.088	.025	.177	.087	.025	.171	.086	.024	.166	.084	.024	.161	.083	.024		
9.0	.169	.082	.023	.167	.081	.023	.161	.080	.023	.157	.078	.022	.152	.077	.022		
10.0	.159	.076	.021	.157	.076	.021	.152	.075	.021	.148	.074	.021	.144	.072	.021		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.178	.156	.137	.152	.134	.118	.104	.092	.082	.060	.053	.047	.019	.017	.015	
2.0	.169	.132	.101	.145	.114	.087	.099	.079	.061	.057	.046	.036	.018	.015	.012	
3.0	.161	.114	.077	.138	.099	.067	.095	.068	.047	.055	.040	.028	.018	.013	.009	
4.0	.154	.101	.060	.132	.087	.052	.091	.061	.037	.052	.036	.022	.017	.012	.007	
5.0	.146	.090	.049	.126	.078	.042	.087	.055	.030	.050	.032	.018	.016	.010	.006	
6.0	.139	.082	.040	.120	.071	.035	.083	.050	.025	.048	.029	.015	.015	.010	.005	
7.0	.133	.075	.034	.114	.065	.030	.079	.045	.021	.046	.027	.013	.015	.009	.004	
8.0	.127	.069	.029	.109	.060	.026	.075	.042	.018	.044	.025	.011	.014	.008	.004	
9.0	.121	.064	.026	.104	.056	.022	.072	.039	.016	.042	.023	.010	.014	.008	.003	
10.0	.115	.060	.023	.099	.052	.020	.069	.037	.014	.040	.022	.008	.013	.007	.003	

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:28 September 2023

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.000m [K=1.0875]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:219.03V I:0.0663A P:14.694W PF:0.9644 Freq:49.99Hz Lamp Flux:1624.07x1 lm		
NAME: GLM-DOS260D-3000K-15W	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	60	49	42	59	49	42	58	48	42	36
0.80	70	59	52	69	59	52	68	58	52	45
1.00	79	68	61	78	68	61	75	69	61	54
1.25	86	76	69	84	75	69	82	74	68	61
1.50	91	82	75	89	81	75	86	79	73	66
2.00	97	89	84	95	88	83	92	86	81	74
2.50	101	94	88	99	92	87	95	90	86	78
3.00	104	98	93	102	96	92	98	93	90	82
4.00	108	103	99	105	101	97	101	98	95	86
5.00	110	106	102	108	104	101	103	100	97	89
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

$H(\beta)$ Range:-90 - 90DEG
 $H(\beta)$ Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:28 September 2023

$V(B)$ Range:-75 - 75DEG
 $V(B)$ Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:8.000m [K=1.0875]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:219.03V I:0.0663A P:14.694W PF:0.9644 Freq:49.99Hz Lamp Flux:1624.07x1 lm		
NAME: GLM-DOS260D-3000K-15W	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:




H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:28 September 2023

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.000m [K=1.0875]
Remarks:

AAI Figure

Test:U:219.03V I:0.0663A P:14.694W PF:0.9644 Freq:49.99Hz Lamp Flux:1624.07x1 lm		
NAME: GLM-DOS260D-3000K-15W	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:28 September 2023

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.000m [K=1.0875]
Remarks:

ISOLUX DIAGRAM

Test:U:219.03V I:0.0663A P:14.694W PF:0.9644 Freq:49.99Hz Lamp Flux:1624.07x1 lm		
NAME: GLM-DOS260D-3000K-15W	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



H(β) Range:-90 - 90DEG
 H(β) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:28 September 2023

V(B) Range:-75 - 75DEG
 V(B) Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:8.000m [K=1.0875]
 Remarks:

LED Avg.L Report

Test:U:219.03V I:0.0663A P:14.694W PF:0.9644 Freq:49.99Hz Lamp Flux:1624.07x1 lm		
NAME: GLM-DOS260D-3000K-15W	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	5984
L_0~180 (75) av	3564
L_0~180 (85) av	0
L_90~270 (65) av	6876
L_90~270 (75) av	5211
L_90~270 (85) av	0
L_45 (65) av	6371
L_45 (75) av	4413
L_45 (85) av	0

Standard: GB/T 29293-2012

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:28 September 2023

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.000m [K=1.0875]
Remarks:

Planar Illuminance Curve



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:28 September 2023

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.000m [K=1.0875]
Remarks:

