

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	6620	6332	6220	6019	6259	6063	6287	6382	0- 10	622.1	622.1	10.6,10.6
20	5289	5274	4991	4769	4831	4853	5103	5377	10- 20	1594	2217	37.9,37.9
30	3288	3178	3268	2903	3049	2983	3400	3297	20- 30	1865	4082	69.8,69.8
40	1213	1228	1217	1157	1133	1227	1251	1339	30- 40	1344	5425	92.7,92.7
50	68.71	241.1	131.9	229.2	41.97	223.6	117.5	230.1	40- 50	378.7	5804	99.2,99.2
60	0.0000	31.55	11.45	27.13	0	10.38	0.0000	13.91	50- 60	43.24	5847	100,100
70	0	0	3.815	0	0	0	0	0	60- 70	2.502	5850	100,100
80	0	0	0	0	0	0	0	0	70- 80	0.0964	5850	100,100
90	0	0	0	0	0	0	0	0	80- 90	0	5850	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 5714.3 lm

%lum = 97.7%

%lamp = 97.7%

Conical surface Flux(120deg): 5847 lm

%lum = 100.0%


%lamp = 100.0%

$H(\beta)$ Range:-90 - 90DEG
 $H(\beta)$ Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:28 February 2025

V(B) Range:-75 - 75DEG
 V(B) Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:8.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:219.79V I:0.1969A P:41.741W PF:0.9646 Freq:49.99Hz Lamp Flux:5849.65x1 lm		
NAME: GLM-PLS128CR1200 (3030CW) 4000K	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	0	0
80	0	0
75	0	0
70	0	74
65	0	119
60	0	152
55	228	822
50	708	1359
45	1743	1788


H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:28 February 2025

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:219.79V I:0.1969A P:41.741W PF:0.9646 Freq:49.99Hz Lamp Flux:5849.65x1 lm		
NAME: GLM-PLS128CR1200 (3030CW) 4000K	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	Coefficients of Utilization(CU)															
RCR:Room Cavity Ratio																
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.11	1.08	1.06	1.09	1.06	1.04	1.05	1.03	1.01	1.01	.00	.98	.97	.96	.95	.94
2.0	1.03	.99	.96	1.01	.98	.95	.98	.95	.93	.95	.93	.91	.92	.90	.89	.87
3.0	.96	.91	.87	.95	.90	.87	.92	.88	.85	.90	.87	.84	.87	.85	.83	.81
4.0	.90	.84	.80	.89	.84	.80	.87	.82	.79	.85	.81	.78	.83	.79	.77	.75
5.0	.84	.78	.74	.83	.78	.74	.81	.77	.73	.80	.76	.72	.78	.75	.72	.70
6.0	.79	.73	.69	.78	.72	.68	.77	.72	.68	.75	.71	.67	.74	.70	.67	.65
7.0	.74	.68	.64	.73	.68	.64	.72	.67	.63	.71	.66	.63	.70	.66	.63	.61
8.0	.70	.64	.60	.69	.63	.59	.68	.63	.59	.67	.62	.59	.66	.62	.59	.57
9.0	.66	.60	.56	.65	.60	.56	.64	.59	.56	.63	.59	.55	.63	.58	.55	.54
10.0	.62	.56	.52	.62	.56	.52	.61	.56	.52	.60	.55	.52	.59	.55	.52	.51



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:28 February 2025

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.000m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:219.79V I:0.1969A P:41.741W PF:0.9646 Freq:49.99Hz Lamp Flux:5849.65x1 lm		
NAME: GLM-PLS128CR1200 (3030CW) 4000K	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.177	.101	.032	.170	.097	.031	.158	.090	.029	.146	.084	.027	.135	.078	.025		
2.0	.170	.093	.029	.164	.090	.028	.154	.085	.027	.144	.081	.025	.135	.076	.024		
3.0	.162	.086	.026	.158	.084	.025	.149	.080	.024	.140	.077	.024	.132	.073	.023		
4.0	.155	.081	.024	.151	.079	.023	.143	.076	.023	.136	.073	.022	.129	.070	.021		
5.0	.148	.075	.022	.145	.074	.022	.138	.072	.021	.131	.069	.021	.125	.067	.020		
6.0	.142	.071	.020	.138	.070	.020	.132	.068	.020	.127	.066	.019	.122	.064	.019		
7.0	.136	.067	.019	.133	.066	.019	.127	.064	.019	.122	.063	.018	.118	.061	.018		
8.0	.130	.063	.018	.127	.063	.018	.123	.061	.017	.118	.060	.017	.114	.059	.017		
9.0	.125	.060	.017	.122	.060	.017	.118	.058	.017	.114	.057	.016	.110	.056	.016		
10.0	.120	.057	.016	.118	.057	.016	.114	.056	.016	.110	.055	.016	.107	.054	.015		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020		
1.0	.171	.157	.145	.146	.135	.125	.100	.093	.086	.058	.054	.050	.018	.017	.016		
2.0	.156	.132	.113	.134	.114	.097	.092	.079	.068	.053	.046	.040	.017	.015	.013		
3.0	.144	.114	.090	.123	.098	.078	.085	.068	.054	.049	.040	.032	.016	.013	.011		
4.0	.134	.099	.072	.115	.085	.063	.079	.060	.044	.046	.035	.026	.015	.011	.009		
5.0	.125	.087	.059	.107	.076	.052	.074	.053	.036	.043	.031	.022	.014	.010	.007		
6.0	.118	.078	.050	.101	.068	.043	.070	.047	.030	.041	.028	.018	.013	.009	.006		
7.0	.112	.071	.042	.096	.061	.036	.066	.043	.026	.039	.025	.015	.012	.008	.005		
8.0	.106	.064	.036	.091	.056	.031	.063	.039	.022	.037	.023	.013	.012	.008	.004		
9.0	.101	.059	.031	.087	.051	.027	.060	.036	.019	.035	.021	.011	.011	.007	.004		
10.0	.096	.055	.027	.083	.048	.024	.058	.034	.017	.034	.020	.010	.011	.007	.003		

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:28 February 2025

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.000m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:219.79V I:0.1969A P:41.741W PF:0.9646 Freq:49.99Hz Lamp Flux:5849.65x1 lm										
NAME: GLM-PLS128CR1200 (3030CW) 4000K					TYPE:LED			WEIGHT:		
SPEC.:					DIM.:			SERIAL No.:1		
MFR.: EVERFINE					SUR.:			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	13.9	14.8	14.1	15.0	15.2	14.4	15.3	14.6	15.5	15.7
3H	13.7	14.6	14.0	14.8	15.0	14.2	15.1	14.5	15.3	15.5
4H	13.6	14.4	13.9	14.7	14.9	14.1	14.9	14.4	15.2	15.4
6H	13.5	14.3	13.8	14.5	14.8	14.0	14.8	14.3	15.0	15.3
8H	13.5	14.2	13.8	14.5	14.7	14.0	14.7	14.3	15.0	15.2
12H	13.4	14.1	13.7	14.4	14.7	13.9	14.6	14.3	14.9	15.2
4H 2H	13.6	14.4	13.9	14.7	14.9	14.1	14.9	14.4	15.2	15.4
3H	13.4	14.1	13.8	14.4	14.7	13.9	14.6	14.3	14.9	15.2
4H	13.3	14.0	13.7	14.3	14.6	13.8	14.5	14.2	14.8	15.1
6H	13.2	13.8	13.6	14.1	14.5	13.7	14.3	14.1	14.6	15.0
8H	13.2	13.7	13.6	14.1	14.4	13.7	14.2	14.1	14.6	14.9
12H	13.1	13.6	13.6	14.0	14.4	13.6	14.1	14.1	14.5	14.9
8H 4H	13.2	13.7	13.6	14.1	14.4	13.7	14.2	14.1	14.6	14.9
6H	13.1	13.5	13.5	13.9	14.3	13.6	14.0	14.0	14.4	14.8
8H	13.0	13.4	13.5	13.8	14.3	13.5	13.9	14.0	14.3	14.8
12H	13.0	13.3	13.4	13.7	14.2	13.5	13.8	14.0	14.2	14.7
12H 4H	13.1	13.6	13.6	14.0	14.4	13.6	14.1	14.1	14.5	14.9
6H	13.0	13.4	13.5	13.8	14.3	13.5	13.9	14.0	14.3	14.8
8H	13.0	13.3	13.4	13.7	14.2	13.5	13.8	14.0	14.2	14.7
Variations with the observer position at spacings:										
S = 1.0H	+ 3.2 / -24.6					+ 2.6 / -15.1				
1.5H	+ 5.8 / -14.4					+ 5.2 / -11.0				
2.0H	+ 5.5 / - 1.5					+ 3.8 / -44.9				

CIE Pub.117, 5850 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 6.1$)

$H(\beta)$ Range:-90 - 90DEG
 $H(\beta)$ Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:28 February 2025

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:219.79V I:0.1969A P:41.741W PF:0.9646 Freq:49.99Hz Lamp Flux:5849.65x1 lm		
NAME: GLM-PLS128CR1200 (3030CW) 4000K	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	87	81	77	86	80	77	86	80	76	73
0.80	95	89	85	94	88	85	93	88	84	81
1.00	99	94	90	98	93	90	97	93	89	85
1.25	103	98	95	102	98	94	100	96	94	89
1.50	106	101	98	105	101	98	103	99	96	92
2.00	109	105	101	107	104	101	105	102	99	94
2.50	110	107	104	109	105	103	106	103	101	95
3.00	112	109	106	110	107	105	107	104	103	96
4.00	114	111	109	112	109	108	108	106	105	98
5.00	115	113	111	113	111	109	109	108	106	99
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

$H(\beta)$ Range:-90 - 90DEG
 $H(\beta)$ Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:28 February 2025

$V(B)$ Range:-75 - 75DEG
 $V(B)$ Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:8.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:219.79V I:0.1969A P:41.741W PF:0.9646 Freq:49.99Hz Lamp Flux:5849.65x1 lm		
NAME: GLM-PLS128CR1200 (3030CW) 4000K	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:




H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:28 February 2025

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.000m [K=1.0000]
Remarks:

AAI Figure

Test:U:219.79V I:0.1969A P:41.741W PF:0.9646 Freq:49.99Hz Lamp Flux:5849.65x1 lm		
NAME: GLM-PLS128CR1200 (3030CW) 4000K	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:28 February 2025

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.000m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:219.79V I:0.1969A P:41.741W PF:0.9646 Freq:49.99Hz Lamp Flux:5849.65x1 lm		
NAME: GLM-PLS128CR1200 (3030CW) 4000K	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:28 February 2025

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.000m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:219.79V I:0.1969A P:41.741W PF:0.9646 Freq:49.99Hz Lamp Flux:5849.65x1 lm		
NAME: GLM-PLS128CR1200 (3030CW) 4000K	TYPE:LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	0
L_0~180 (75) av	0
L_0~180 (85) av	0
L_90~270 (65) av	59
L_90~270 (75) av	0
L_90~270 (85) av	0
L_45 (65) av	86
L_45 (75) av	0
L_45 (85) av	0

Standard: GB/T 29293-2012

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:28 February 2025

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.000m [K=1.0000]
Remarks:

Planar Illuminance Curve



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:28 February 2025

V(B) Range:-75 - 75DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:8.000m [K=1.0000]
Remarks:

