


Ceiling ,Wall Luminaires

GLM-DOR260D




Produktmerkmale

Modle NO	GLM-DOR260D
Size	Φ260*57mm
Input Power	8/10/15W
Current	115/140/200mA
lumen Efficiency	120LM/W
Lumens Output	960/1200/1800LM
AC Input	AC200-240V
LED	SMD2835
Number of LED	384
Driver	AGT
Ra	80/90
CCT	3/4/6000K
SDCM	<3
Frequency	50/60Hz
Output Voltage	DC60-72V
Power Factor	>0.9
THD	<15%
Power Efficiency	>87%
Operating Temperature	-20°C-45°C
Storage Temperature	-20°C-60°C
Operating Humidity	90%Rh or below(@-20°C-45°C)
Application Area	Indoors
Lifespan	50,000HS
Relevant	EN55015,EN61347-1


Description

- Circular LED wall lights and polycarbonate lampshades for ceiling lights,
 - A simple lamp installation adapter can be installed on walls or ceilings.
 - Double sided fast shutter, suitable for tool free illumination housing installation
- On the adapter.
- LED-SMD technology on metal core board has good heat dissipation performance
 - The color temperature of 3000K or 4000K or 6000K can be adjusted by sliding
- Before installation, turn on the back of the light.
- Ra 90 color reproduction.
 - Adjustable to 8 watts, 10 watts, or 15 watts.
 - Pressing type terminal block, luminous flux 960-1800lm depending on color
- Temperature and power.
- Size: Φ 260 * 57 millimeters.
 - Impact strength IK10, protection level IP54.
 - The service life of this product is 50000 hours (L80 | B10). CE mark.
- ENEC certification.
- Standards: EN 60598-1, EN 60598-2-1,
 - EN 62471, EN 62493, EN 55015, EN 61000-3-2
 - EN 610-3-3, EN 61547

Light Distribution



Energy Efficiency Rating



Shenzhen Gleamia Lighting

☎ Tel: +86-755-89589529 ☎ Fax: +86-755-89507460 ☎ Email: mark@gleamia.net ☎ Web: www.gleamia.net

📍 Add: 2nd Floor, Block C, Building 1, Hisense Science & Technology Park, Longgang, Shenzhen, China