

LED Ceiling Light

GLM-PLS128CR1200

Product Features

Model	GLM-PLS128CR1200
Size	L1155*W130*H47mm
AC Input	AC220-240V
Input Power	30W-36W-42W
Current	250mA-300mA-350mA
Lumens Output	3900Lm-4680Lm-5460Lm
CCT	3/4/6000K
lumen Efficiency	130LM/W
LED	SMD2835
Number of LED	320
Driver	TRIDONIC
Ra	80/90
SDCM	<3
Frequency	50/60Hz
Output Voltage	DC50-133V
Power Factor	>0.9
THD	<20%
Power Efficiency	>90%
Operating Temperature	-20°C-45°C
Storage Temperature	-20°C-60°C
Operating Humidity	90%Rh or below(@-20°C-40°C)
Application Area	Indoors
Lifespan	50,000HS
Relevant	EN55015,EN61347-1

Description

- LED wall and ceiling lights with polycarbonate light shields and reflective cups,
 - A simple installation adapter for installing lights can be installed on walls or ceilings.
 - Double sided shutter, used for installing toolless lighting housings on adapters.
 - This board adopts metal core LEDSM technology with good performance
 - Heat dissipation and color temperature adjustable from 3000 to 4000 or 6000K
- Before installation, the sliding switch on the rear light is adjustable.

-Ra 90

-Press type terminal, adjustable 30W, 36W or 42W, luminous flux 3900-5460lm

It depends on color temperature and power.

Size: L1155 * W130 * H47mm

Impact resistance strength LK10, protection level IP54.

-The service life of this product is 50000 hours (L80B10)


-CE mark, ENEC certification.

Standard: EN 60598-1, EN 60598




Model NO	GLM-PLS-EL1200	GLM-PLS-EL1200DA	GLM-PLS-EL1200S	GLM-PLS-EL1200P
Size	Electrical box- Tridonic Driver	Electrical box- BOKE DALI Driver	Philips driver+ Sensor box	Tridonic driver +Indirect light+suspension wire

Light Distribution



Energy Efficiency Rating



Shenzhen Gleamia Lighting

Tel: +86-755-89589529 Fax: +86-755-89507460 Email: mark@gleamia.net Web: www.gleamia.net

Add: 2nd Floor, Block C, Building 1, Hisense Science & Technology Park, Longgang, Shenzhen, China