


Ceiling ,Wall Luminaires

GLM-DOS300D




Produktmerkmale

Modle NO	GLM-DOS300D
Size	300*300*57mm
Input Power	8/10/15W
Current	115/140/280mA
AC Input	AC200-240V
lumen Efficiency	120LM/W
Lumens Output	960/1200/1800LM
LED	SMD2835
Number of LED	576
Driver	AGT
Ra	80/90
CCT	3/4/6000K
SDCM	<3
Frequency	50/60Hz
Output Voltage	DC60-72V
Power Factor	>0.9
THD	<15%
Power Efficiency	>87%
Operating Temperature	-20°C-45°C
Storage Temperature	-20°C-60°C
Operating Humidity	90%Rh or below(@-20°C-45°C)
Application Area	Indoors
Lifespan	50,000HS
Relevant	EN55015,EN61347-1


Description

- Square LED wall lights and polycarbonate lampshades for ceiling lights,
- A simple lamp installation adapter can be installed on walls or ceilings.
- Double sided fast shutter, suitable for tool free illumination housing installation On the adapter.
- LED-SMD technology on metal core board has good heat dissipation performance
- The color temperature of 3000K or 4000K or 6000K can be adjusted by sliding
- Before installation, turn on the back of the light.
- Ra 90 color reproduction.
- Adjustable to 8 watts, 10 watts, or 15 watts.
- Pressing type terminal block, luminous flux 960-1800lm depending on color Temperature and power.
- Size: 300 * 300 * 57 millimeters.
- Impact strength IK10, protection level IP54.
- The service life of this product is 50000 hours (L80 | B10). CE mark.
- ENEC certification.
- Standards: EN 60598-1, EN 60598-2-1,
- EN 62471, EN 62493, EN 55015, EN 61000-3-2
- EN 610-3-3, EN 61547

Light Distribution



Energy Efficiency Rating



Shenzhen Gleamia Lighting

☎ Tel:+86-755-89589529 ☎ Fax:+86-755-89507460 ✉ Email:mark@gleamia.net 🌐 Web:www.gleamia.net
 📍 Add:2nd Floor,Block C,Building 1,Hisense Science & Technology Park,Longgang, Shenzhen,China